

# Full Color IP Camera



## ARNKL500WH-B

- Full Color Bullet
- 1/2.8" SONY Starves Back-illuminated CMOS sensor
- H.264/H.265/JPEG/AVI Compression Method
- 3.6mm Fixed Lens
- Support Warm white (4000K), up to 40m
- With Internal POE

<b>SPECIFICATION</b>	
<b>Model NO.</b>	<b>ARNKL500WH-B</b>
<b>Camera</b>	
<b>Image Sensor</b>	1/2.8" SONY Starves Back-illuminated CMOS sensor
<b>Resolution</b>	5MP
<b>Effective Pixels</b>	2616 (H)*1964 (V)
<b>Compression</b>	H.264/H.265/JPEG/AVI
<b>Audio Compression</b>	G711A/U,AAC
<b>TV System</b>	PAL/NTSC
<b>Electronic Shutter Time</b>	Auto: 1/3-1/100000Sec
<b>Minimun Illumination</b>	Color: 0.006 Lux @ (F1.6, AGC ON),B/W: 0 Lux with white light
<b>S/N Ratio</b>	≥52dB
<b>Scanning System</b>	Progressive
<b>Video Output</b>	Network
<b>Reset Button</b>	Optional
<b>Lens</b>	
<b>Focus Length</b>	Board Lens 3.6mm
<b>Focus Control</b>	Fixed
<b>Lens Type</b>	Fixed
<b>Pixels</b>	5MP
<b>Night Vision</b>	
<b>Infrared LED</b>	No, Support Warm light LED 4000K, up to 40m
<b>Infrared Distance</b>	N/A
<b>IR Status</b>	Auto Control
<b>IR Power On</b>	Smart, Manual & Timed mode
<b>Network</b>	
<b>Ethernet</b>	RJ-45 (10/100Base-T)
<b>Wireless</b>	N/A
<b>Protocol</b>	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP ,PPPoE, NTP, SMTP, UDP, SNMP
<b>ONVIF</b>	Support ONVIF 19.12(Profile S/T/G)
<b>P2P</b>	YES
<b>POE</b>	Internal, Support IEEE 802.3af
<b>Video Delay</b>	0.3S (Within the Lan)
<b>Main Stream 1</b>	2592*1944@30fp
<b>Main Stream 2</b>	2560*1440@30fp
<b>Main Stream 3</b>	1920*1080@30fps 1280*720@30fps
<b>Sub Stream 1</b>	1280*720@30fps
<b>Sub Stream 2</b>	720*480@30fps
<b>Sub Stream 3</b>	N/A
<b>Tri Stream</b>	N/A
<b>IE Brower</b>	IE8-11, Google Chrome, Firefox , Mac Safari
<b>Smart Phone</b>	iPhone, Android
<b>AI Function</b>	
<b>Intelligent Analysis</b>	Intrusion Detection, Line Cross Detection, Loiter Detection, People Gather Detection(based on human detection),Motion detection based on human detection

<b>Camera Features</b>	
<b>Day/Night</b>	Color
<b>Image Config</b>	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control),Occlusion Detection,HLC
<b>Full Color</b>	Support
<b>Corridor Pattern</b>	Support
<b>Defog Mode</b>	N/A
<b>ROI</b>	Support
<b>BLC</b>	Support
<b>WDR</b>	120dB
<b>Motion Detection</b>	Support(support enable the detection based on human movement only)
<b>Privacy Masking</b>	3 Rectangular Zone
<b>Recording Mode</b>	NVR/CMS/Web
<b>Language</b>	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands,Czech, Vietnamese
<b>Interface</b>	
<b>Audio</b>	Optional 1 Built-in MIC
<b>Alarm</b>	N/A
<b>SD Card Slot</b>	Optional Internal, Support Max 512GB
<b>RS485</b>	N/A
<b>General</b>	
<b>Housing</b>	Cover: Plastic Main Body: Metal, IP67
<b>Anti-cut Bracket</b>	NO
<b>IR Cut Filter</b>	YES
<b>Operation Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 1000mA
<b>Dimension</b>	268(W) x 95(H) x 88(D)mm
<b>Weight</b>	1500g
<b>Certification</b>	CE, EAC, ROHS

**Dimension:** (mm)

